

Preliminary Datasheet

Laser Projector

NEC UM504HL

Benefits

Great picture quality – thanks to 1080p resolution and 10000:1 contrast.

Almost no shadow and glare – thanks to ultra-short throwing distance.

Black and White cabinet versions – matching installations demanded by Museum, Leisure, Signage and Higher Education applications

Specifications

Product Information

Product Name

NEC UM504HL

Product Group

Laser Projector

Order Code

60005472(WH), 60005470(BK)

Image

Projection Technology

1-chip DLP™ Technology

Native Resolution

1920 x 1080 (FULL-HD)

Aspect Ratio

16:9

Contrast Ratio

100000:1

Brightness

(TBD) Normal / (TBD) Lumen Eco; (TBD) Centre Lumen

Lens

F= (TBD), f= (TBD) mm

Keystone Correction

+/- 30° manual horizontal / +/- 30° manual vertical

Projection Angle [°]

(TBD)

Projection Factor

0.23 : 1

Projection Distance [m]

0.008 – 0.045

Screen Size (diagonal) [cm] / [inch]

Maximum: 381 / 150"; Minimum: 203 / 80"

Zoom

Digital Zoom

Focus Adjustment

Manual

Supported Resolutions

1024 x 768 (XGA);	1360 x 768 (WXGA);	1920 x 1080 (HDTV 1080i/60;
1152 x 864 (XGA);	1366 x 768 (WXGA);	HDTV 1080i/50);
1152 x 870 (MAC 21");	1400 x 1050 (SXGA+);	640 x 480 (VGA/ MAC 13");
1280 x 1024 (MAC 23");	1440 x 900 (WXGA+);	720 x 480 SDTV 576p/576i;
1280 x 1024 (SXGA);	1600 x 1200 (UXGA);	720 x 576 SDTV 480p/480i;
1280 x 720 (HDTV 720p);	1600 x 900 (WXGA++);	800 x 600 (SVGA);
1280 x 768 (WXGA);	1680 x 1050 (WSXGA+);	832 x 624 (MAC 16")
1280 x 800 (WXGA);		
1280 x 960 (SXGA);		

Frequency

Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz

Connectivity

RGB (analog)

Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr)

Output: 1 x Mini D-sub 15 pin

Digital

Input: 2 x HDMI™ (Deep Color, Lip sync)

Video

Input: 1 x RCA

Audio

Input: 1 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo

Output: 1 x 3.5 mm Stereo Mini Jack (variable)

Control

Input: 1 x D-Sub 9 pin (RS-232) (male)

LAN

1 x RJ45

USB

1x Type A (USB 2.0 high speed) with 1.5A Power Supply

Video Signals

NTSC; NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Remote Control

Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Direct Source Select; Freeze; Help Eco Mode; Help-function; ID set; Picture Adjust; Presentation and Mouse Control

Electrical

Power Supply

100-240 V AC; 50 - 60 Hz

Power Consumption [W]

(TBD) (Normal) / (TBD) (Eco) / (TBD) (Network Stand-by) / (TBD) (Stand-by)

Mechanical

Dimensions (W x H x D) [mm]

509 x 145 x 390 (without lens and feet)

Weight [kg]

(TBD)

Fan Noise [dB (A)]

34 / 37 (Eco / Normal)

Colour Versions

Black; White

Environmental Conditions

Operating Temperature [°C]

0 to 40

Operating Humidity [%]

20 to 80 non-condensing

Storage Temperature [°C]

-10 to 50

Storage Humidity [%]

20 to 80 non-condensing

Ergonomics

Safety and Ergonomics

CE; ErP; RoHS; TÜV GS

Speakers [W]

1 x 10 (mono)

Additional Features

Special Characteristics

3D ready; AMX Beacon; Auto Eco Mode; Auto Power ON/OFF; Crestron RoomView; DICOM simulation; Direct Power-Off Function; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify; Manual vertical Keystone Correction ($V = \pm 5^\circ$); NaViSet Administrator 2; Off-Timer; Optional User Logo; OSD with 30 languages; Password Security System; PJ LINK; Quick On/Off; Remote control and administration via LAN and RS232; Security Bar; Test Pattern; Wall Colour Correction

Green Features

Ecological Materials

100% recyclable packaging; Downloadable manuals; ECO packaging

Ecological Standards

ErP compliant; RoHS compliant

Warranty

Projectors

3 years pan-European service

Shipping Content

Shipping Content

3x AAA Batteries; IR Remote Control (RD469E); Power Cord; Quick Setup Guide; Security Sticker

Optional Accessories

Optional Accessories

Manual Height Adjustable Wall Mount (TBD)

* This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG2 of IEC62471-5 Ed1 2015.
DO NOT LOOK DIRECTLY INTO THE BEAM.



RoHS



TÜV GS



CE



ErP

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers.
All specifications are subject to change without notice. Errors and omissions are excepted. 24.09.2026