

50" Digital Signage Display

Sharp / NEC MultiSync ME501

Ihr Weg zur digitalen Beschilderung.



- Modern and slim design – robust yet elegant allowing for an unobtrusive integration into any application and environment.
- Ease of use and operation – smart installation, operation and maintenance functionality ensures accurate performance over the entire lifetime of the display saving time, effort and resources.
- Effortless content playback – the integrated USB media player supports various image video file formats for effortless and standalone content playback.
- Secure remote management – control your devices remotely and securely using NEC NaviSet Administrator 2; proactively manage maintenance requirements saving time and resources.
- Future Ready Connectivity – featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

Technische Daten

DISPLAY

Bildschirmtechnologie	VA with Direct LED backlights
Native Auflösung (Pixel)	3840 x 2160
Diagonale (Zoll / cm)	50 / 125.7
Seitenverhältnis	16:9
Helligkeit (cd/m2)	400
Kontrastverhältnis	≥ 8000:1
Reaktionszeit [ms]	8
Betrachtungswinkel (H/V) 0 CR> 10	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

STROMVERSORGUNG UND BETRIEBSUMGEBUNG

Betriebsspannung (ACV) / Frequenz (Hz)	100-240 V AC; 50 / 60 Hz
Leistungsaufnahme (W) (Betrieb MAX.)	85 shipping
Betriebstemperatur (oC)	0 to 40
Feuchtigkeit (%)	20 to 80

INSTALLATION

Querformat	•
Hochformat	•
Montage (VESA/Anzahl Punkte/Abstand mm)	4 holes; 400 x 400 (FDMI)

KONNEKTIVITÄT (AUDIO/VIDEO) AUSGANG

Audio/Kopfhörer 3,5-mm-Buchse	1
-------------------------------	---

ZUBEHÖR

Fernbedienungssender	Yes
Netzkabel	Yes
Befestigungskonsole	Optional
Tischstativ	Optional

ECKWERTE

Begrenzte Herstellergarantie (in Jahren).	3
Integrierte Lautsprecher (W)	10 W + 10 W
Power-Management	•
Gehäusefarbe	Black
Temperaturfühler	•

MAßE UND GEWICHTE

Bezel-Größe (L/R) mm	14.9
Bezel-Größe (U/L) mm	14.9
Produktabmessungen (B/H/T) mm	1,128.4 x 649 x 62.6
Versandkarton-Abmessungen (B/H/T) mm	1,298 x 860 x 224
Produktgewicht ohne Stativ (kg)	17.3
Versandgewicht (kg)	24.1

KONNEKTIVITÄT (AUDIO/VIDEO) EINGANG

HDMI	2
DisplayPort	1
Audio 3,5-mm-Buchse	1

KONNEKTIVITÄT (STEUERUNG/SERIELLE DATEN)

RS232C Eingang	1
LAN-Anschluss	1
USB	1

